




ISO 2768-2 K																
Range	0-10	>10-30	>30-100	>100-300	>300-1000	>1000-3000	0-100	>100-300	>300-1000	>1000-3000						
Tolerance	0.05	0.1	0.2	0.4	0.6	0.8	0.4	0.6	0.8	1						0.2
Default tolerance except material stock dimensions																
ISO 2768-1 m Linear							Radii and Chamfers			Angular Dimensions						
Range	>0.5-6	>6-30	>30-120	>120-400	>400-1000	>1000-2000	>2000	>0.5-3	>3-6	>6	0-10	>10-50	>50-120	>120-400	>400	
Toler.	±0.1	±0.2	±0.3	±0.5	±0.8	±1.2	±2	±0.2	±0.5	±1	±1°	±0.5°	±0.32°	±0.16°	±0.08°	

-	PRIMA EMISSIONE		FedericoZoppetti		18/05/2022						
REV	Description			Designed		Date		Released		Date	
 DieTronic lubricating technology			Raw material: -			 FIRST ANGLE PROJ.		 ISO 13715		Weight 176,68	
			Surface treatment: -								
			Heat treatment: -								
			Material -			Scale 1 : 3		Sheet size A2		Sheet 4 / 4	
			Description Plate 45x30 L=4745			Part number S001148				Rev. -	

This document contains CONFIDENTIAL proprietary information which shall NOT be used, reproduced, or disclosed without prior written approval of Dietronic s.r.l. Notice ISO 16016.

This document contains CONFIDENTIAL proprietary information which shall NOT be used, reproduced, or disclosed without prior written approval of Dietronic s.r.l. Notice ISO 16016.