




A

ISO 2768-2 K															
Range	0-10	>10-30	>30-100	>100-300	>300-1000	>1000-3000	0-100	>100-300	>300-1000	>1000-3000					
Tolerance	0.05	0.1	0.2	0.4	0.6	0.8	0.4	0.6	0.8	1	0.2				
Default tolerance except material stock dimensions															
ISO 2768-1 m Linear							Radii and Chamfers			Angular Dimensions					
Range	>0.5-6	>6-30	>30-120	>120-400	>400-1000	>1000-2000	>2000	>0.5-3	>3-6	>6	0-10	>10-50	>50-120	>120-400	>400
Toler.	±0.1	±0.2	±0.3	±0.5	±0.8	±1.2	±2	±0.2	±0.5	±1	±1°	±0.5°	±0.32°	±0.16°	±0.08°

-	PRIMA EMISSIONE		B2FT	22/06/2022	
REV	Description		Designed	Date	Released
 DieTronic lubricating technology	Raw material: Piatto trafilato 110x30 h11		 FIRST ANGLE PROJ.	 ISO 13715	Weight 4,986
	Surface treatment: -				
	Heat treatment: -				
	Material 1.0037 - Acciaio S235JR		Scale 1 : 1.5	Sheet size A3	Sheet 1 / 1
	Description Lift Plate		Part number 5300937		Rev.
This document contains CONFIDENTIAL proprietary information which shall NOT be used, reproduced, or disclosed without prior written approval of Dietronic s.r.l. Notice ISO 16016.					