





ELECTRICAL CONNECTION (AT CUSTOMER CHARGE):
MAIN POWER 3 PHASES: 400V 50hz 25Kw
UPS POWER: 24VDC 20A
UPS POWER: 220VDC

PN/PN Coupler (dietronic supply - Connection with the DST excluded)

ISO 2768-2 K												
Range	0-10	>10-30	>30-100	>100-300	>300-1000	>1000-3000	0-100	>100-300	>300-1000	>1000-3000		
Tolerance	0.05	0.1	0.2	0.4	0.6	0.8	0.4	0.6	0.8	1	0.2	
Default tolerance except material stock dimensions												
ISO 2768-1 m Linear							Radii and Chamfers			Angular Dimensions		
Range	>0.5-6	>6-30	>30-120	>120-400	>400-1000	>1000-2000	>2000	>0.5-3	>3-6	>6	0-10	>10-50
Toler.	±0.1	±0.2	±0.3	±0.5	±0.8	±1.2	±2	±0.2	±0.5	±1	±1°	±0.5°
											±0.32°	±0.16°
												±0.08°

-	PRIMA EMISSIONE	Zoppetti	05/04/2022		
REV	Description	Designed	Date	Released	Date
 	Raw material:	 FIRST ANGLE PROJ.	 ISO 13715	Weight	
	Surface treatment:			9660,069	
	Heat treatment:				
	Material	Scale 1 : 100	Sheet size A3	Sheet 1 / 1	
	Description Combi 4000 - Main Power Supply	Part number 2022856	Rev.		
This document contains CONFIDENTIAL proprietary information which shall NOT be used, reproduced, or disclosed without prior written approval of Dietronic s.r.l. Notice ISO 16016.					