





ISO 2768-2 K																														
Range	0-10		>10-30		>30-100		>100-300		>300-1000		>1000-3000		0-100		>100-300		>300-1000		>1000-3000											
Tolerance	0.05		0.1		0.2		0.4		0.6		0.8		0.4		0.6		0.8		1		0.2									
Default tolerance except material stock dimensions																														
ISO 2768-1 m Linear												Radii and Chamfers					Angular Dimensions													
Range	>0.5-6		>6-30		>30-120		>120-400		>400-1000		>1000-2000		>2000		>0.5-3		>3-6		>6		0-10		>10-50		>50-120		>120-400		>400	
Toler.	±0.1		±0.2		±0.3		±0.5		±0.8		±1.2		±2		±0.2		±0.5		±1		±1°		±0.5°		±0.32°		±0.16°		±0.08°	

-	PRIMA EMISSIONE				FedericoZoppetti		10/06/2024			
REV	Description				Designed		Date		Released	
 		Raw material:			 FIRST ANGLE PROJ.		 ISO 13715		Weight	
		Surface treatment:							22,21	
		Heat treatment:								
		Material			Scale 1 : 3		Sheet size A2		Sheet 1 / 1	
		Description Speed MCL 300 - Lubricator (up to 12mm)			Part number G000000				Rev. -	
This document contains CONFIDENTIAL proprietary information which shall NOT be used, reproduced, or disclosed without prior written approval of DieTronic s.r.l. Notice ISO 16016.										

This document contains CONFIDENTIAL proprietary information which shall NOT be used, reproduced, or disclosed without prior written approval of Dietronic s.r.l. Notice ISO 16016.